



Adjunct Professor, University of Canterbury, Christchurch, New Zealand


















ANTERBURY

"Our" understading of Earthquake-Resistant





Which means..... from the point of view of a Structural Engineer....





PwC-22-storeys emulative precast concrete post-1980s Precast or cast-in-place column unit Midspan Cast-in-place concrete Cast-in-place Mortar or and top steel in beam grout joint Precast or Precast beam uni cast-in-place column unit (b) System 2 - Precast Beam Units Through Columns



Extensive damage (beyond reparability?) to modern Buildings



Typical **plastic hinges** in beams (intended to act as sacrificial fuses)








Computer Modeling of Plastic Hinge (Research collaboration with University of Stuttgart, Germany) ut Sat MASA3 R4endeB00 ate[2.024]; Tistal nodal disp tour: Avra E11 stra






A very common end : Man-made Demolition




As per 12 June 2011 Source: CCC Data (Kam, Pampanin, Elwood, 2012)

"But they [buildings] did what they were meant to do"
















The Code-Standard is **NOT** meant to be used as a Target or Ultimate Goal but as a <u>minimum</u> by law

¥

Corollary

Earthquake-Resistant


(earthquake engineering community's view)

Earthquake-Proof


(everyone else's view)




The Renewed Challenge of Eartquake Engineering: Raising the bar to meet Society's Expectations




















able 2.2 NZS Recommendat		Risk Cl	assifica	tions and	Impro	ve	ment	New Zealand Socie for Earthqua Engineeri de de d
Description	Grade	Risk	%NBS	Existing Building Structural Performance			Improvement of Str	uctural Performat
						-	Legal Requirement	NZSEE Recommendati
Low Risk Building	A or B	Low	Above 67	Acceptable (improvement may be desirable)			The Building Act sets no required level of structural improvement	100%NBS desira Improvement sh achieve at lea 67%NBS
Noderate Risk Building	B or C	Moderate	34 to 66	Acceptable legally. Improvement recommended			(unless change in use) This is for each TA to decide. Improvement is not limited to 34%NBS.	Not recommend Acceptable only exceptional circumstance
High Risk Building	D or E	High	33 or lower	Unacceptable (Improvement required under Act)		-	Unacceptable	Unacceptable











Italian Seismic Risk Classification (2017)

1) (Life) Safety Index (%NBS, IS-V)


2) Economic Losses Index (EAL)

ITA2017 Matrix – IS-V(=%NBS), Risk Class, EAL/PAM

IS-V	IS-V ranges	EAL	EAL ranges
Class	_	Class	_
$A^{+}_{\text{IS-V}}$	IS-V >100	A^{+}_{PAM}	EAL ≤0.5%
A_{IS-V}	$80\% \le IS-V \le 100\%$	A_{PAM}	$0.5\% < EAL \le 1.0\%$
B _{IS-V}	60%≤I S-V< 80%	B_{PAM}	$1.0\% < EAL \le 1.5\%$
C_{IS-V}	45%≤ IS-V< 60%	C_{PAM}	$1.5\% \le EAL \le 2.5\%$
D_{IS-V}	$30\% \le IS-V \le 45\%$	D_{PAM}	$2.5\% < EAL \le 3.5\%$
E_{IS-V}	15%≤ IS-V< 30%	E_{PAM}	3.5%< EAL ≤4.5%
F_{IS-V}	IS-V < 15%	F_{PAM}	$4.5\% < EAL \le 7.5\%$
	-	G_{PAM}	7.5%≤EAL

Financial Incentives from the IT Government (Tax Rebate up to 85% or 110% of the Retrofit costs)
















Prof. Dr. Eng. Stefano Pampanin















Prof. Dr. Eng. Stefano Pampanin














Prof. Dr. Eng. Stefano Pampanin






Terremoto 2002, immagine San Giuliano di Puglia




















Prof. Dr. Eng. Stefano Pampanin










The Opportunity for the Future: **Cost-efficient low-damage technology Base Isolation** PRESSS-Technology (An Internal Isolation?) (Southern Cross Hospital Endoscopy Building) (Christchurch Women Hospital) Unbonded post-tensioned tendons Energy Dissipation Devices












A1 Autore, 16/10/2008




Prof. Dr. Eng. Stefano Pampanin





Christchurch Vision 2050: Re-building a resilient city with low- damage technology







Low-Damage Technologies Concrete, Timber, Steel and combinations










Towards the "Ultimate Earthquake Proof-building" Shake-table testing of an integrated low-damage system



Johnston, Watson, Pampanin, Palermo (2013, 2014)



Next Generation of Integrated Low-Damage Building with dry jointed ductile connections





























3D shake-table testing campaign can be found at:

https://www.youtube.com/watch?v=RHczItvneug&t=558s



I August 2019 – Lisbon (PT)


TRIDIRECTIONAL TEST XYZ LIMIT STATE 4

Christchurch (NZ) February 22, 2011 Mw = 6.3 Station = CCCC Depth = 5 km Distance = 3.8 km Scaling Factor = 1.2 PGA = 0.58 g









Prof. Dr. Eng. Stefano Pampanin

